

**WHITE FEET TILE** <sup>®</sup>  
ISO 9001:2015

The Cool Roof Tiles Expert...




**WHITE FEET - COOL ROOF TILES**

HEAT RESISTANT | WATER PROOF | ANTI-SKID | WASH PROOF

LIGHT WEIGHT | LOW COST | SAVES ELECTRICITY

**WHITE FEET TILE** <sup>®</sup>

The Cool Roof Tiles Expert...



“**ENGAGE THE EVEREST  
ON TOP OF YOUR  
ROOF AND TERRACE**”



# WHITE FEET - COOL ROOF TILES

## About Us

**White Feet Tile Industry established in the year 2013 and became the renowned manufacturers of Cool Roof Tiles in the tiles industry, our products are best in quality and price.**

**We are having well qualified professionals with well maintained factory space to make the product well. We are also having our own Transport facility for on time delivery of material for hassle free site laying works.**

## MISSION

**“ We Continuously Support The Eco Friendly Environment in The World by Our Products “**

## VISION

**“ We create Products Which Makes Development in the Tiles Industry and Improvement To Society “**

## Advantages

- ◆ Protect building From Thermal Impact
- ◆ No need to put Weathering Course
- ◆ Less usage of Fans / Air Conditioner
- ◆ Cost Effective
- ◆ High Durability
- ◆ Easy Maintenance
- ◆ Anti-Skid, Water Resistant
- ◆ 100% Washable
- ◆ Non Ceramic material
- ◆ User friendly
- ◆ Good Antifungal Property
- ◆ Good Abrasion Resistance
- ◆ Semi Gloss Surface



# WHITE FEET TILE



## Our Products

Model : Silver Plus

254mm X 254mm X 15mm



<https://whitefeetile.in>



Protect from thermal impact



No need of weathering course



Water Resistance

Model : Mx-Chempro

254mm X 254mm X 18mm



<https://whitefeetile.in>



Protect from thermal impact



No need of weathering course



Water Resistance



# WHITE FEET TILE



Model : Mx-Prime

254mm X 254mm X 18mm



<https://whitefeetile.in>



Protect from thermal impact



No need of weathering course



Water Resistance

Model : Elite silver

300mm X 300mm X 20mm



<https://whitefeetile.in>



Protect from thermal impact



No need of weathering course



Water Resistance



# WHITE FEET TILE



Model : Elite Gold

300mm X 300mm X 20mm



<https://whitefeetile.in>



Protect from thermal impact



No need of weathering course



Water Resistance

Model : Parking Tile

356mm X 356mm X 25mm



Faimi  
Silver Grey & Dark Grey

## Features of Parking Tiles :

- Durability
- Slip Resistance
- Stain Resistance
- Weather Resistance
- Low Maintenance
- Design Options
- Strength



# WHITE FEET TILE



## White Feet Grout

Weight 10 Kg



<https://whitefeettile.in>

White feet sanded grout is made of blended portland cement, graded aggregates, fortifiers and pigments, it provides a tile joint that is strong, hard, durable and colourfast.

## White Feet Grout admix

250 ml



<https://whitefeettile.in>

Grout Admix is specially designed latex admix to be used with sanded & unsanded grout.

Mixing Ratio:

Use approximately 2 to 2.25 litres of water mixed with 250ml admix for 10kg Rough Grout.



# WHITE FEET TILE



## White Feet IWP

5 L



<https://whitefeettile.in>

Whitefeet IWP is liquid concrete waterproofing admixture formulated from selected polymers specially designed to reduce the concrete water permeability by reducing capillary voids within the concrete, which will last for the life of the concrete.

## White Feet Spacer

250 ml




<https://whitefeettile.in>

- White, square tile with smooth, heat-reflective surface.
- 6 mm groove for water drainage and proper alignment.
- Ideal for homes, flats, and rooftop cooling.



# WHITE FEET TILE



## TESTIMONIALS

**OMEGA INSPECTION & ANALYTICAL LABORATORY**  
 ISO / IEC : 17025 : 2005 Accredited by NABL, Dept. of Science & Technology, Govt. of India

T.S. No. 57 & 58, Guindy Industrial Estate, Guindy, Chennai - 600 032, INDIA. Phone : 044 - 2250 0127  
 Telefax : 044 - 2250 0523, Mobile : 94442 55041. E-mail : omega\_lal@outlook.com Web : www.omegalab.in

TOCR NO. 19- 6381  
 TR.No.01- 15278 - 1

Page 1/1  
 Date: 24.01.19

**Test Report**  
 On Roofing Tiles

To,  
 M/s. White Feet Tile Industry  
 No.350/1, Kundrathur Main Road,  
 Kovur, Chennai - 600 122.

Source of sample : Sample drawn by the customer  
 Customer Reference \* : No.Nil, Dtd.18.01.19  
 Project \* : Not Furnished  
 Make \* : White Feet - Silver Plus (255 x 255 x 16mm)  
 No. of Samples Tested : 3 Nos  
 Period of test : 18.01.19 to 23.01.19  
 Technical Reference : ASTM E 1980 & IS: 15622 -2006

Sl. No	Tested Parameters	Results		
		Low-Wind	Medium-Wind	High-Wind
1.	Solar Reflectance Index (SRI)	87	89	90

\* As furnished by the customer

**Results:** All measurements were conducted at 72±3°F and 50±5%RH.

Note(s): 1- Reflectance measurements were conducted using a Devices and Services SSR-ER Version 6.4 Reflectometer operated in v5 emulation mode and calibrated with Devices and Services Reference Tile # D-18.  
 2- Emittance measurements were conducted using a Devices and Services Emissometer Model AE calibrated with Devices and Services Reference Standards: High Emittance: 0.90 and Low Emittance: 0.06. Thermal emittance measurement for sample was modified in accordance with Devices and Services Company's Tech Note 04-1.  
 3- SRI calculations per ASTM E 1980 utilize the following assumptions: Low-Wind h = 5 W/m-K, Medium-Wind h = 12 W/m-K, and High-Wind h = 30 W/m-K.

*P. Kabilan*  
 Engineer  
 Tested/Verified

for Omega Inspection & Analytical Laboratory  
 (K.M. Balasubramanian)  
 Chief Executive Officer

Note: Certified that the test enumerated above have been carried out in conformity with standard testing procedures and relevant specifications. The Certificate refers ONLY to the particular sample(s) submitted for test. Sample description is not verified in all cases and is given as described by customer. All complaints about this should be communicated in writing within 10 days from the date of issue of this report. The report shall be reproduced in Part/all, without the approval of OIAL.

Silver Plus Test Report

**OMEGA INSPECTION & ANALYTICAL LABORATORY**  
 ISO / IEC : 17025 : 2005 Accredited by NABL, Dept. of Science & Technology, Govt. of India

T.S. No. 57 & 58, Guindy Industrial Estate, Guindy, Chennai - 600 032, INDIA. Phone : 044 - 2250 0127  
 Telefax : 044 - 2250 0523, Mobile : 94442 55041. E-mail : omega\_lal@outlook.com Web : www.omegalab.in

TOCR NO. 19- 6119  
 TR.No.01- 14644

Page 1/1  
 Date: 09.01.19

**Test Report**  
 On Roofing Tiles

To,  
 M/s. White Feet Tile Industry  
 No.350/1, Kundrathur Main Road,  
 Kovur, Chennai - 600 122.

Source of sample : Sample drawn by the customer  
 Customer Reference \* : No.Nil, Dtd.02.01.19  
 Project \* : Not Furnished  
 Make \* : White Feet Gold (255 x 255 x 16mm)  
 No. of Samples Tested : 3 Nos  
 Period of test : 02.01.19 to 09.01.19  
 Technical Reference : ASTM E 1980 & IS: 15622 -2006

Sl. No	Tested Parameters	Results		
		Low-Wind	Medium-Wind	High-Wind
1.	Solar Reflectance Index (SRI)	89	91	90

\* As furnished by the customer

**Results:** All measurements were conducted at 72±3°F and 50±5%RH.

Note(s): 1- Reflectance measurements were conducted using a Devices and Services SSR-ER Version 6.4 Reflectometer operated in v5 emulation mode and calibrated with Devices and Services Reference Tile # D-18.  
 2- Emittance measurements were conducted using a Devices and Services Emissometer Model AE calibrated with Devices and Services Reference Standards: High Emittance: 0.90 and Low Emittance: 0.06. Thermal emittance measurement for sample was modified in accordance with Devices and Services Company's Tech Note 04-1.  
 3- SRI calculations per ASTM E 1980 utilize the following assumptions: Low-Wind h = 5 W/m-K, Medium-Wind h = 12 W/m-K, and High-Wind h = 30 W/m-K.

*M. D. Ram Kumar*  
 Engineer  
 Tested/Verified

for Omega Inspection and Analytical Laboratory  
 (K.M. Balasubramanian)  
 Chief Executive Officer

Note: Certified that the test enumerated above have been carried out in conformity with standard testing procedures and relevant specifications. The Certificate refers ONLY to the particular sample(s) submitted for test. Sample description is not verified in all cases and is given as described by customer. All complaints about this should be communicated in writing within 10 days from the date of issue of this report. The report shall not be reproduced in Part/all, without the written approval of OIAL.

Mx Prime Test Report



# WHITE FEET TILE

## TESTIMONIALS

**OMEGA INSPECTION & ANALYTICAL LABORATORY**

Our Esteemed Customers : HYUNDAI, FORD, NISSAN, TOYOTA, MAHINDRA & MAHINDRA, WIPRO, IRR, DGBA, BHEL, BY IRS, BIS, EIL, LLOYDS, NLC, RITES, CPWD, CMSSB, PWD, TN&D, AAI, S.R.I.V., PORT TRUST, WABARD, NHAI, MILITARY (MES), Etc.,

T.S. No. 35.38 & 57.58 Guindy Industrial Estate, Guindy, Chennai 600 032, INDIA. Phone : 044 2250 0127  
Telefax : 044 - 2250 0523, Mobile : 94442 55041, E-mail : omega\_ial@outlook.com Web : www.omegalab.in

TOCR NO. 20- 1262  
TR.No.09- 2450 A

Date: 16.09.2020

### Test Report

**On Roofing Tiles**

To,  
M/s. White Feet Tile Industry  
No.350/1, Kundrathur Main Road,  
Kovur, Chennai - 600 122.

Source of sample : Sample drawn by the customer  
Customer Reference \* : No.NIL, Dtd.09.09.2020  
Project \* : Not Furnished  
Make \* : Elite - Silver (300 x 300 x 20mm)  
No. of Samples Tested : 3 Nos  
Period of test : 10.09.20 to 16.09.20  
Technical Reference : ASTM E 1980 & IS: 15622 -2006

Sl. No	Tested Parameters	Results		
		Low-Wind	Medium-Wind	High-Wind
1.	Solar Reflectance Index (SRI)	90	92	95

\* As furnished by the customer

**Results:** All measurements were conducted at 72±3°F and 50±5%RH.

Note(s): 1- Reflectance measurements were conducted using a Devices and Services SSR-ER Version 6.4 Reflectometer operated in v5 emulation mode and calibrated with Devices and Services Reference Tile # D-18.  
2- Emittance measurements were conducted using a Devices and Services Emissometer Model AE calibrated with Devices and Services Reference Standards: High Emittance: 0.90 and Low Emittance: 0.06. Thermal emittance measurement for sample was modified in accordance with Devices and Services Company's Tech Note 04-1.  
3- SRI calculations per ASTM E 1980 utilize the following assumptions: Low-Wind h = 5 W/m.K, Medium-Wind h = 12 W/m.K, and High-Wind h = 30 W/m.K.

for Omega Inspection & Analytical Laboratory  
(K.M.Balasubramanian)  
Chief Executive Officer

Note: Certified that the test enumerated above have been carried out in conformity with standard testing procedures and relevant specifications. The Certificate refers ONLY to the particular sample(s) indicated for test. Sample description is not verified in all cases and is given as described by customer. All complaints about this should be communicated in writing within 10 days from the date of issue of this report. This report shall be reproduced intact in Part III, without the approval of OIAL.

Elite Silver Test Report

**OMEGA INSPECTION & ANALYTICAL LABORATORY**

Our Esteemed Customers : HYUNDAI, FORD, NISSAN, TOYOTA, MAHINDRA & MAHINDRA, WIPRO, IRR, DGBA, BHEL, BY IRS, BIS, EIL, LLOYDS, NLC, RITES, CPWD, CMSSB, PWD, TN&D, AAI, S.R.I.V., PORT TRUST, WABARD, NHAI, MILITARY (MES), Etc.,

T.S. No. 35.38 & 57.58 Guindy Industrial Estate, Guindy, Chennai 600 032, INDIA. Phone : 044 2250 0127  
Telefax : 044 - 2250 0523, Mobile : 94442 55041, E-mail : omega\_ial@outlook.com Web : www.omegalab.in

TOCR NO. 20- 1262  
TR.No.09- 2451 A

Date: 16.09.2020

### Test Report

**On Roofing Tiles**

To,  
M/s. White Feet Tile Industry  
No.350/1, Kundrathur Main Road,  
Kovur, Chennai - 600 122.

Source of sample : Sample drawn by the customer  
Customer Reference \* : No.NIL, Dtd.09.09.2020  
Project \* : Not Furnished  
Make \* : Elite - Gold (300 x 300 x 20mm)  
No. of Samples Tested : 3 Nos  
Period of test : 10.09.20 to 16.09.20  
Technical Reference : ASTM E 1980 & IS: 15622 -2006

Sl. No	Tested Parameters	Results		
		Low-Wind	Medium-Wind	High-Wind
1.	Solar Reflectance Index (SRI)	92	95	97

\* As furnished by the customer


**Results:** All measurements were conducted at 72±3°F and 50±5%RH.

Note(s): 1- Reflectance measurements were conducted using a Devices and Services SSR-ER Version 6.4 Reflectometer operated in v5 emulation mode and calibrated with Devices and Services Reference Tile # D-18.  
2- Emittance measurements were conducted using a Devices and Services Emissometer Model AE calibrated with Devices and Services Reference Standards: High Emittance: 0.90 and Low Emittance: 0.06. Thermal emittance measurement for sample was modified in accordance with Devices and Services Company's Tech Note 04-1.  
3- SRI calculations per ASTM E 1980 utilize the following assumptions: Low-Wind h = 5 W/m.K, Medium-Wind h = 12 W/m.K, and High-Wind h = 30 W/m.K.

for Omega Inspection & Analytical Laboratory  
(K.M.Balasubramanian)  
Chief Executive Officer

Note: Certified that the test enumerated above have been carried out in conformity with standard testing procedures and relevant specifications. The Certificate refers ONLY to the particular sample(s) indicated for test. Sample description is not verified in all cases and is given as described by customer. All complaints about this should be communicated in writing within 10 days from the date of issue of this report. This report shall be reproduced intact in Part III, without the approval of OIAL.

Elite Gold Test Report



# WHITE FEET TILE



## ISO CERTIFICATE

**Certificate**



**Certificate of Registration**

*This is to Certify that  
Quality Management System of*

**WHITE FEET TILE INDUSTRY**

S. NO.350/1, KUNDRATHUR MAIN ROAD, KOVUR,  
CHENNAI - 600122, TAMIL NADU, INDIA

Has been independently assessed and is compliant  
with the requirements of  
**ISO 9001:2015**

for the following scope :


MANUFACTURERS AND SUPPLIERS OF COOL ROOF TILES

Certificate No : 21/Q/WHF0701      Issuance Date : 01/07/2024  
Initial Registration Date : 01/07/2024      Date of Expiry : 30/06/2027

  
Auth. Signatory




**Times Certification Services UK Ltd.**  
Regd Office : 71-75 Shelton Street, Covent Garden, London, WC2H 9JQ, United Kingdom  
This certificate is the Intellectual Property of Times Certification Services UK Ltd, can be maintained through surveillance audit and  
renewal audit. Certificate shall be voided immediately on request in case of non-compliance of Certification Procedure.  
Validity of this certificate can be verified at : [www.timescert.co.uk](http://www.timescert.co.uk) or via email at [info@timescert.co.uk](mailto:info@timescert.co.uk)



# WHITE FEET TILE

## Comparison Chart


 <b>White Feet Tile Industry</b>	<b>Silver plus</b>	<b>Elite Silver</b>	<b>Mx-Chempro</b>	<b>Mx-Prime</b>	<b>Elite Gold</b>
<b>Size</b>	254mm X 254mm X 15mm	300mm X 300mm X 20mm	254mm X 254mm X 18mm	254mm X 254mm X 18mm	300mm X 300mm X 20mm
<b>Color</b>	Top White Bottom Grey	Top White Bottom Grey	Top White Bottom Grey	Full White	Full White
<b>Model Highlight</b>	Top 7mm Cooling Minerals Balance 8mm Concrete	Top 10mm Cooling Minerals Balance 10mm Concrete	Top 9 mm Cooling Minerals Balance 9 mm Concrete	18mm Full Cooling Minerals	20mm Full Cooling Minerals
<b>Area Coverage</b>	0.69 sqft	1.00 sqft	0.69 sqft	0.69 sqft	1.00 sqft
<b>Weight</b>	2 Kg Per Tile	4 Kg Per Tile	2.25 Kg Per Tile	2.25 Kg Per Tile	4 Kg Per Tile
<b>Water Absorption</b>	3.58 % ( Not more than 10% )	3 % ( Not more than 10% )	3.58 % ( Not more than 10% )	3.02 % ( Not more than 10% )	2.55 % ( Not more than 10% )
<b>Solar Reflective Index ( SRI ) Value</b>	89 ( Medium Wind )	92 ( Medium Wind )	89 ( Medium Wind )	91 ( Medium Wind )	95 ( Medium Wind )



# WHITE FEET TILE


## PACKING SYSTEM






# WHITE FEET TILE





# WHITE FEET TILE






# WHITE FEET TILE


## SITE GALLERY





# WHITE FEET TILE





# WHITE FEET TILE



## Laying Instructions for Cool Roof Tiles

- 1) Prepare base mortar with cement and sand in the ratio 1:4 along with waterproofing chemicals.
- 2) The total mortar thickness should not be more than 25mm.
- 3) Keep the hand mixer ready to apply to avoid uneven surface, while laying the tile.
- 4) Prepare cement slurry as thick paste to spread on the mortar.
- 5) Use a 6mm spacer in between tiles.
- 6) Do not use a hammer for laying.
- 7) Fill the joints with white cement, sand and water proofing chemicals or use suitable waterproofing grouting Materials.
- 8) Do not use the layed area for 48 hours.

Google

Reviews

Customer Rating



# WHITE FEET TILE

ISO 9001:2015

The Cool Roof Tiles Expert...

Factory/ Office :

No:350/ 1, Kundrathur Main Road,  
Kovur, Chennai-600122



[whitefeettile@gmail.com](mailto:whitefeettile@gmail.com)



[www.whitefeettile.in](http://www.whitefeettile.in),  
[www.whitefeet.in](http://www.whitefeet.in)



[@WhiteFeetCoolRoofTiles](https://www.youtube.com/@WhiteFeetCoolRoofTiles)



[facebook.com/CoolRoofTiles/](https://facebook.com/CoolRoofTiles/)



[instagram.com/cool\\_roof\\_tiles/](https://instagram.com/cool_roof_tiles/)



# CONTACT: +91 98845-20001